

PR-7000 CE

Hinged system.

The ability to adapt to the aesthetic and functional needs of each building is essential in architecture. The PR-7000 CE system was designed to be one of the most versatile hinged window systems available. Its simple design adds value to the great versatility of all its functions.



Features

- Euro Groove hardware
- Concealed hardware and micro-ventilation option
- Choice of straight or curved sash
- Triple gasket seal



TECHNICAL FEATURES

Design

The PR-7000 CE system was designed to be one of the most versatile hinged window systems available. Its simplicity adds value to the great versatility of all its functions.

Features

Simple and versatile, this 40 mm deep range is highly adaptable to the aesthetic and functional requirements of any building. It also offers a triple seal.

Benefits

Air permeability, watertightness and wind load resistance testing of this system achieves air permeability Class 3, water resistance Class E1050 and wind load resistance Class C4. The PR-7000 CE window system is ideal for warm climates.

Possibilities

The PR-7000 CE is one of the most versatile systems available. It allows glazing up to 36 mm and provides the most common opening types.



Max. recommended dimensions (LxH)*	1400x2300 mm
Maximum recommended weight**	130 kg/sash
Maximum glazing	36 mm
Frame depth	40 mm
Thermal insulation U_w ***	Up to 2,5 W/m ² K

Weather test results for a 1230x1480 mm 2-sash window with roller shutter casement

* For a 1 sash window

** Depending on the dimensions and type of opening

*** For a 1 sash window 1100x2200 mm

