

Classic CE

Hinged system
with thermal break.

One of Exlabesa's most complete and versatile window systems. The Classic aluminium window has a wide variety of profiles that complete the system to make it a safe bet for any type of building.



Features

- Euro Groove hardware
- Concealed hardware and micro-ventilation option
- Choice of straight or curved sash
- Indoor or outdoor opening



TECHNICAL FEATURES

Design

This is a range with a modern style that is suitable for all types of buildings. Its straight lines give the set a sobriety and elegance that can be combined with any material.

Features

The Classic CE system uses 16 mm polyamide and is an industry benchmark with a frame depth of 52 mm. Its sections are assembled by direct screwing.

Benefits

The performance of the Classic CE is undisputed, reaching Class 4, E1650 and CE3100 in air permeability, watertightness and wind load resistance tests.

Possibilities

The Classic CE hinged window offers all types of solutions: exterior, interior, door, projecting, pivoting, etc. It has a variety of complementary profiles that allow it to be adapted to the specific needs of each project.



Max. recommended dimensions (LxH)*	1400x2300 mm
Maximum recommended weight**	130 kg/sash
Maximum glazing	49 mm
Polyamide	16 mm
Thermal insulation U_w ***	Up to 1,4 W/m ² K
Thermal insulation U_f	3,5 W/m ² K

Weather test results for a 1230x1480 mm 2-sash window with roller shutter casement

* For a 1 sash window

** Depending on the dimensions and type of opening

*** For a 1 sash window 1100x2200 mm

