

## PR-7000 CE

Hinged system.

The ability to adapt to the aesthetic and functional needs of each building is essential in architecture. The PR-7000 CE system was designed to be one of the most versatile hinged window systems available. Its simple design adds value to the great versatility of all its functions.



### Features

- Euro Groove hardware
- Concealed hardware and micro-ventilation option
- Choice of straight or curved sash
- Triple gasket seal



# TECHNICAL FEATURES

## Design

The PR-7000 CE system was designed to be one of the most versatile hinged window systems available. Its simplicity adds value to the great versatility of all its functions.

## Features

Simple and versatile, this 40 mm deep range is highly adaptable to the aesthetic and functional requirements of any building. It also offers a triple seal.

## Benefits

Air permeability, watertightness and wind load resistance testing of this system achieves air permeability Class 4, water resistance Class E900 and wind load resistance Class C5. The PR-7000 CE window system is ideal for warm climates.

## Possibilities

The PR-7000 CE is one of the most versatile systems available. It allows glazing up to 36 mm and provides the most common opening types.



Max. recommended dimensions (LxH)*	1400x2300 mm
Maximum recommended weight**	130 kg/sash
Maximum glazing	36 mm
Frame depth	40 mm
Thermal insulation $U_w$ ***	Up to 2,5 W/m <sup>2</sup> K

Weather test results for a 1230x1480 mm 2-sash window

\* For a 1 sash window

\*\* Depending on the dimensions and type of opening

\*\*\* For a 1 sash window 1100x2200 mm

