

CONFORMITY CERTIFICATE OF FACTORY PRODUCTION CONTROL

Certificate No: 1035-CPR-ES106804

In compliance of the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonized conditions for the marketing of construction products, it has been stated that the product:

ALUMINIUM AND ALUMINIUM ALLOYS STRUCTURAL PRODUCTS FOR CONSTRUCTION WORKS

Manufactured by: EXLABESA EXTRUSIÓN PADRÓN, S.L.

Social address: POL. IND. QUINTÁ, LUGAR A PICARAÑA, S/N

15980 - PADRÓN - A CORUÑA (SPAIN)

In the factory: 1.- POL. IND. QUINTÁ, LUGAR A PICARAÑA, S/N

15980 - PADRÓN - A CORUÑA (SPAIN)

2.- CRUCES

15980 - ROIS - A CORUÑA (SPAIN)

They are submitted by the manufacturer to the initial type testing of the product and a factory production control, and that the notified body Bureau Veritas Certification has performed the initial inspection of the factory and of the factory production control and performs the continuous surveillance, assessment and approval of the factory production control established in the harmonized standard concerned.

This certificate attests that all provisions concerning the attestation of factory production control described in the Annex ZA of the harmonized standard concerned, and it authorizes the manufacturer or its agent to fix the CE marking.

This certificate remains valid as long as the conditions laid down in the harmonised standard concerned or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Initial date of issue: 2019 / 09 / 12 Date of update: 2025 / 09 / 12 Expiration date: 2028 / 09 / 11



Mónica Botas

Certification Manager





ANNEX TO CERTIFICATE No: 1035-CPR-ES106804

Date: 2025 / 09 / 12

EN 15088:2005. Aluminium and aluminium alloys. Structural products for construction works. Technical conditions for inspection and delivery. Descripción: EXTRUDED PROFILE **ALLOY TREATMENT** PROFILE DIMENSIONS LENGTH **THICKNESSES** T5 - T6 - T66 AW6060 AW6063 T4 -T5 - T6 - T66 Profiles inscribed in a circle **Products** Thicknesses between AW6061 T6 with a diameter 0,8 and 50 mm up to 14 m from 6 to 620 mm AW6005A T6 AW6082 T5 - T6

Technical conditions for inspection and delivery. Descripción: EXTRUDED TUBE **ALLOY TREATMENT DIAMETERS TUBES** LENGTH **THICKNESSES** AW6060 T5 - T6 -T66 AW6061 T6 AW6101B **T6** Tubes inscribed in a circle **Products** Thicknesses between AW6063 T5 - T6 -T66 with a diameter up to 14 m 0,8 and 50 mm

from 6 to 380 mm

EN 15088:2005. Aluminium and aluminium alloys. Structural products for construction works.



T6

T6

AW6005A

AW6082

(In Dota

Mónica Botas Certification Manager





ANNEX TO CERTIFICATE No: 1035-CPR-ES106804

Date: 2025 / 09 / 12

		N 15088:2005. Aluminium and aluminium alloys. Structural products for construction works. Technical conditions for inspection and delivery				
	Descripción: EXTRUDED BAR					
	ALLOY	TREATMENT	DIAMETERS BAR	LENGTH	THICKNESSES	
	AW6005A	T6	Bars inscribed in a circle with a diameter from 6 to 150 mm	Products up to 14 m	Thicknesses between 6 and 150 mm	
	AW6082	T6				





Bureau Veritas Iberia, S.L., C/ Valportillo Primera 22-24 28108 - Alcobendas (MADRID). Notified Body 1035