

Glass Rail inFix PRO

Glass Juliet balcony.

The Glass Rail inFix PRO Juliet balcony redefines the interior space experience by combining protection, light, and design. Its high-strength glass provides complete safety, while installation in front of the window frame preserves the visual connection with the exterior and enhances the sense of space.

With a minimalist design focused on practicality, it allows the glass to be mounted from the front and is compatible with any window frame. Installation is quick and easy thanks to the use of universal screws and the elimination of reinforcement plates, simplifying both cutting and assembly processes.

Glass Rail inFix PRO combines the classic beauty of the Juliet balcony with modern technology, ensuring safety, ease of installation, and a flawless finish that enhances every project.



Features

- Exclusive profiles with a 48 mm visible front
- Compatible with any window frame
- Glass can be mounted from the front
- Suitable for multiple glass thicknesses
- Use of universal screws during installation
- Greater efficiency in cutting and assembly thanks to the elimination of reinforcement plates
- Tested according to CTE for private use (0.8 kN/m) and public use (1.6 kN/m)



TECHNICAL FEATURES

◆ Design

With a 48 mm visible front, the exclusive design of **Glass Rail inFix PRO** combines minimalism and distinction, tailored for the most demanding projects seeking personality, style, and a sophisticated finish that makes a difference.

◆ Features

The **Glass Rail inFix PRO** Juliet balcony combines aluminum profiles and glass to provide maximum safety and a seamless visual connection between interior and exterior. The glass can be easily mounted from the front, making installation faster and more convenient. Additionally, cutting and assembly processes are streamlined and simplified thanks to the elimination of reinforcement plates and the use of universal screws.

◆ Performance

The **Glass Rail inFix PRO** system has been tested in accordance with CTE regulations, making it suitable for installation in both private and public spaces, as well as in all types of building projects, ensuring maximum safety and reliability for users. This railing is certified for annealed laminated glass of 12.38 mm and 16.38 mm, with dimensions up to 2500 mm wide and 1100 mm high, allowing flexible adaptation to the requirements of each project.

◆ Possibilities

The **Glass Rail inFix PRO** glass railing offers multiple glazing options and adapts to any window frame, combining versatility, safety, and ease of installation.



Recommended maximum dimensions (LxH)	2500x1100 mm
Installation	Front
Load (CTE)	0,8 kN/m 1,6 kN/m
Glazing	12,38 to 12,76 mm 16,38 to 16,76 mm 20,38 to 20,76 mm

