

Patio PRO

Bioclimatic Pergola

The Patio PRO bioclimatic pergola transforms any outdoor area into a comfortable, versatile and protected living space throughout the year. Its advanced design combines aesthetics and technology to deliver precise control over light, shade and ventilation.

Its adjustable louvres, with an opening range from 0° to 135°, allow the environment to be intuitively regulated depending on weather conditions and the time of day. The fully concealed motor can be operated through automatic sensors or via a remote-control system, ensuring both convenience and discretion.

Capable of reaching spans of more than 7 meters without intermediate posts and available in multiple installation configurations — including wall-mounted setups with invisible anchoring — Patio PRO stands out for its minimalist aesthetics and robust structure. Its high-quality finishes, customizable LED lighting and details such as hidden screws or splash-guard gutter profiles create a balanced, fully integrated solution for any outdoor setting.



Features

- Spans of more than 7 meters with no intermediate posts
- Fully concealed fastening system with no visible screws between profiles
- Flexible configuration: corner posts, offset posts or invisible wall anchoring
- Fully concealed integrated motor
- Optional lighting: LED strips or LED spotlights
- Gutters with splash-guard profiles
- Functional posts separating electrical wiring and drainage systems
- Refined aesthetics with finishing profiles included





TECHNICAL CHARACTERISTICS

Design

The Patio PRO bioclimatic pergola offers a refined aesthetic, featuring a concealed fastening and screw system that ensures a clean and uniform structure. Its finishing profiles complete the assembly with an elegant appearance, and its 280 mm or 245 mm beams allow for easy adaptation to any project.

Features

This system incorporates integrated gutters with a splash-guard profile that effectively protects the area from rain, optional LED lighting, and functional posts that separate electrical and hidden drainage for enhanced safety and cleaner aesthetic.



Performance

The Patio PRO bioclimatic pergola integrates adjustable louvres with a rotation range from 0° to 135°, allowing precise regulation of light entry and ventilation according to weather conditions. The concealed motor controls their movement automatically through sensors or manually via remote control, providing comfortable and efficient operation.



Possibilities

Patio PRO adapts to any space thanks to its versatile structure. It allows configurations with corner posts, offset posts for a more open design or direct wall installation through an invisible anchoring system that preserves its sophisticated aesthetics.



Maximum dimensions per module	4500x7192 mm
Maximum height	2780 mm
Louvre rotation	0° - 135°
Rainwater drainage	Through the posts (independent)
Motorisation	1200 N concealed motor









